

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 January 2006 (12.01.2006)

PCT

(10) International Publication Number  
WO 2006/004259 A1

(51) International Patent Classification<sup>7</sup>: H01L 21/3065

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/KR2005/000860

(22) International Filing Date: 24 March 2005 (24.03.2005)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:

10-2004-0020321 25 March 2004 (25.03.2004) KR

(71) Applicant (for all designated States except US): ADAPTIVE PLASMA TECHNOLOGY CORPORATION [KR/KR]; 1 Yeongtong-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-808 (KR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KIM, Nam-hun [KR/KR]; 804-302 Byeokjeokgol Dusan Apt., 973-3 Yeongtong-dong, Paldal-gu, Suwon-si, Gyeonggi-do 442-470 (KR).

(74) Agent: AJU INTERNATIONAL LAW & PATENT GROUP; 12th Floor, Poonglim Building, 823-1 Yeoksam-dong, Kangnam-gu, Seoul 135-784 (KR).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PLASMA CHAMBER HAVING PLASMA SOURCE COIL AND METHOD FOR ETCHING THE WAFER USING THE SAME



(57) Abstract: A plasma chamber having a plasma source coil includes a chamber body, a plasma source coil, and an edge bushing. The chamber body includes a reaction space, which is limited by a sidewall, a lower exterior wall, and an upper dome, and forms plasma. The plasma source coil arranged on the dome includes M unit coils corresponding to an integer greater than "2". The M unit coils having a predetermined turning number "n" indicative of a positive integer are extended from a center bushing having a predetermined radius at a center part, and are spirally arranged along a circumference of the center bushing, such that the plasma is formed in the reaction space. The edge bushing arranged between the dome of the chamber body and the plasma source coil, and is configured in the form of a cylindrical shape to overlap with an edge of the wafer arranged in the reaction space.

WO 2006/004259 A1

Express Mail No. E1809338217 US